Specialty Gas Equipment



Single-Stage Brass Regulators

Description: This general-purpose, single-stage regulator is well suited for closely monitored, short run work. The stainless steel diaphragm makes it suitable for analytical applications. The regulator has a compact design to reduce weight and make the regulator more durable. The external chrome plating allows the exterior surfaces to maintain a good appearance in outdoor environments. Nickel plating of the internal gas path surfaces makes it an excellent choice for analytical applications. A preset safety relief valve makes these regulators suitable for use only with noncorrosive gases.

General-Purpose Brass

ANALYTIC SERIES
PRESSURE REGULATORS



Design Features

Filtered Seat (10 micron)

for added gas stream purity and extended service life.

Convoluted Stainless Steel Diaphragms (302 SS) provide precise pressure control.

Large, 21/2" Nickel-Plated Brass Gauges

for accurate, easy reading.

Outlet Needle Valve

Preset Safety Relief Valve

prevents excessive pressure buildup.

Encapsulated Filtered Seat Assy

protect parts, extend service life.

Chrome Nickel-Plated Bar Stock Body provides long-lasting good looks; will not tarnish.

Two (2) 10-32 Taps

for rear mounting.

Specifications	
Maximum Rated Inlet Pressure	3,500 psig
Outlet Pressure Ranges	0-25, 0-50, 0-100, 0-250 psig
Flow Capacity	Cv=0.17
Ambient Operating Temperature	-40° F to +165° F
Designed Leak Rate	Bubble-Tight (helium)
Weight	3.5 lbs
Ports (5)	1/4" FNPT
Inlet	1/4" FNPT
Outlet	1/4" MNPT
Decay Inlet Characteristic	1.8 psi/100 psi

Materials	
Body	Chrome Nickel-Plated Brass
Bonnet	Chrome Plated Die Cast
Seat	PTFE
Diaphragm	302 Stainless Steel
Gauges	21/2" Nickel-Plated Brass
Filter	Nickel-Plated Bronze
Valve Stem	316 Stainless Steel
Valve Spring	18-8 Stainless Steel
Outlet Valve	Nickel-Plated Brass
Trim	Nickel-Plated Brass

Ordering Information						
Product Number	Material	Max Inlet Pressure (psig)	Max Outlet Pressure (psig)	Capacity (scfh @ Max Del. Pressure)	Delivery Gauge Range (psig)	
Y11-AS215A (CGA)	Brass	3,000	25	500	0-30	
Y11-AS215B (CGA)	Brass	3,000	50	810	0-60	
Y11-AS215D (CGA)	Brass	3,000	100	1,350	0-200	
Y11-AS215F (CGA)	Brass	3,000	250	1,720	0-400	

Available Options		
Product Number	Description	
Y99-26120	1/4" FNPT x 1/4" Compression Brass	
Y99-26140	1/4" FNPT x □" Compression Brass	
Y99-CKCGA	Check Valve CGA Connection	