

Sulfur Hexafluoride (SF₆)

- Other balance gases and cylinder sizes are available upon request.
- Concentrations over 10.5% are provided at reduced pressure and volume.

Sulfur Hexafluoride in Nitrogen

Concentration	Cylinder Size	≈Contents ft ³
0.5 ppm - < 100 ppm	200	215
	150A	144
	80	85
	35	33
100 ppm - < 1%	200	215
	150A	144
	80	85
	35	33
1% - 10.5%	200	227
	150A	144
	80	90
	35	33

Primary Standards available for concentrations greater than 1 ppm.
Standard Valve Outlet: CGA 580
Individual Certificate of Analysis or Certificate of Batch Analysis included.

Technical Data & Shipping Information

Cylinder Pressure	2000 psig
U.S. DOT Class	2.2
U.S. DOT Label	Nonflammable Gas
ID Number	UN1956

Equipment Recommendations are found on page 38

Toluene (C₆H₅CH₃)

- Other balance gases and cylinder sizes are available upon request.
- Concentrations over 150 ppm are provided at reduced pressure and volume.

Toluene in Nitrogen

Concentration	Cylinder Size	≈Contents ft ³
0.5 ppm - < 100 ppm	150A	146
	80A	79
	33A	33
100 ppm - 150 ppm	150A	146
	80A	79
	33A	33

Primary Standards available for concentrations greater than 20 ppm
Standard Valve Outlet: CGA 350
Individual Certificate of Analysis included.

Technical Data & Shipping Information

Cylinder Pressure	2000 psig
U.S. DOT Class	2.2
U.S. DOT Label	Nonflammable Gas
ID Number	UN1956

Equipment Recommendations are found on page 38